



Application No.: 10/602216  
 Docket No.: AD6892USNA

Page 2

### Amendments to Claims

Claims 1-10 (Previously Cancelled).  
 Claims 11-17 (Previously Cancelled).

Claims 18 (New) An interlining comprising a laminate produced by bonding and laminating a nonwoven fabric with a nonporous waterproof and windproof moisture-permeable hydrophilic film with a hot melt adhesive layer dispersed and coated over less the entire surface of said fabric, and another hot melt adhesive layer attached on a surface of either the fabric side or the film side, which is to laminate with another fabric or base material, but which covers less than the full surface thereof wherein the film is made of a polyesterether elastomer prepared by ester linkages between long-chain ester repeating units of formula (I) below and short-chain ester repeating units of formula (II) below.



wherein:

- a) G is a divalent radical remaining after the removal of terminal hydroxyl groups from a poly(alkylene oxide)glycol having a number average molecular weight of about 400-4000;
  - b) R is a divalent radical remaining after removal of carboxyl groups from a dicarboxylic acid having a molecular weight less than 300;
  - c) D is a divalent radical remaining after removal of hydroxyl groups from a diol having a molecular weight less than about 250; optionally
  - d) the copolyetherester contains 0-68 weight percent based on the total weight of the copolyetherester, ethylene oxide groups incorporated in the long-chain ester units of the copolyetherester; and
  - e) the copolyetherester contains about 25-80 weight percent short-chain ester units
- and said interlining has a water vapor transmission rate, as measured by method A-1 described in section 4.1.1 or JIS L-1099, of 1,000 to 20,000 g/m<sup>2</sup>.24 h; an air

Application No.: 10/602216  
Docket No.: AD6892USNA

Page 3

permeability, as measured according to JIS L-1018, of up to 30 cm<sup>3</sup>/cm<sup>2</sup>/s; and a water pressure resistance, as measured according to JIS L-1092, of 100 to 40,000.

Claim 19 (Currently Canceled)

Claims 20. (Currently Amended) A garment or fabric which uses the interlining of aforementioned ~~new~~ claim 18.